



APS Automotive Enterprises Co.,Ltd.

A2, 2ND Floor, Main Building, 33 Changhong Road, Modern Logistics Park, Xiamen, China 361006

Tel: 86-592-5619 592 86-592-2620 070 Fax: 86-592-5610884 E-mail: aa@aaps.cn / karl@cps.cn

<http://www.apspart.com>

<http://apsparts.en.alibaba.com/index.html>

Type 1 H-Beam Connecting Rods

APS P/N	Length	BE Bore (mm)		PIN Bore (mm)		Bolts	Gram Weight
		Dia	Height	Dia	Height		
H-4353VW	137.01±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.04}	Ø22 ^{+0.012} ₀	24.7 ⁰ _{-0.04}	5/16 200K	2.6kg
H-4354VW	137.16±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.04}	Ø22 ^{+0.012} ₀	24.7 ⁰ _{-0.04}	5/16 200K	2.6kg
H-4355VW	139.7±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.04}	Ø22 ^{+0.012} ₀	24.7 ⁰ _{-0.04}	5/16 200K	2.7kg
H-4356VW	142.24±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.04}	Ø22 ^{+0.012} ₀	24.7 ⁰ _{-0.04}	5/16 200K	2.9kg
H-4354C	137.16±0.03	Ø53.968 ^{+0.008} _{-0.005}	22.53 ⁰ _{-0.04}	Ø21.996±0.005	25.27 ⁰ _{-0.04}	5/16 200K	2.6kg
H-4355C	139.7±0.03	Ø53.968 ^{+0.008} _{-0.005}	22.53 ⁰ _{-0.04}	Ø21.996±0.005	25.27 ⁰ _{-0.04}	5/16 200K	2.7kg
H-4356C	142.24±0.03	Ø53.968 ^{+0.008} _{-0.005}	22.53 ⁰ _{-0.04}	Ø21.996±0.005	25.27 ⁰ _{-0.04}	5/16 200K	2.9kg
H-4357C	144.78±0.03	Ø53.968 ^{+0.008} _{-0.005}	22.53 ⁰ _{-0.04}	Ø21.996±0.005	25.27 ⁰ _{-0.04}	5/16 200K	3.0kg

Type 1 I-Beam Connecting Rods

APS P/N	Length	BE Bore (mm)		PIN Bore (mm)		Bolts	Gram Weight
		Dia	Height	Dia	Height		
131 4154VW B	137.01±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.05}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.1}	3/8	2.4kg
131 4154VW	137.16±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.05}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.1}	3/8	2.5kg
131 4155VW	139.7±0.03	Ø57.8±0.005	22.65 ⁰ _{-0.05}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.1}	3/8	2.6kg
131 4154C B	137.01±0.03	Ø53.975 ^{+0.0127} _{-0.0076}	22.53 ⁰ _{-0.038}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.04}	3/8	2.6kg
131 4154C	137.16±0.03	Ø53.975 ^{+0.0127} _{-0.0076}	22.53 ⁰ _{-0.038}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.04}	3/8	2.6kg
131 4155C	139.7±0.03	Ø53.975 ^{+0.0127} _{-0.0076}	22.53 ⁰ _{-0.038}	Ø22 ^{+0.012} ₀	25.27 ⁰ _{-0.04}	3/8	2.6kg

Type 4 H-Beam Connecting Rods

APS P/N	Length	BE Bore (mm)		PIN Bore (mm)		Bolts	Gram Weight
		Dia	Height	Dia	Height		
H-5. 158	131. 01±0. 03	Ø52. 8 ^{+0. 012} ₀	25. 7±0. 02	Ø24 ^{+0. 012} ₀	26. 77±0. 005	5/16 200K	2. 1kg
H-5. 325	135. 26±0. 03	Ø52. 8 ^{+0. 012} ₀	25. 7±0. 02	Ø22. 009 ^{+0. 013} ₀	26. 77±0. 005	5/16 200K	2. 4kg